

FAX TRANSMISSION**DATE:** February 23, 2010**PTO IDENTIFIER:** Application Number 10/593,036-Conf. #5742
Patent Number**Inventor:** Kenji SUZUKI et al.**MESSAGE TO:** US Patent and Trademark Office - Examiner H. Sayadian**FAX NUMBER:** 571-273-7779**FROM:** BIRCH, STEWART, KOLASCH & BIRCH, LLP

Vanessa Perez

PHONE: (703) 205-8000**Attorney Dkt. #:** 1592-0165PUS**PAGES (Including Cover Sheet):** 5**CONTENTS:** Attached are our proposed claim amendments (not for entry).

If your receipt of this transmission is in error, please notify this firm immediately by collect call to sender at (703) 205-8000 and send the original transmission to us by return mail at the address below.

This transmission is intended for the sole use of the individual and entity to whom it is addressed, and may contain information that is privileged, confidential and exempt from disclosure under applicable law. You are hereby notified that any dissemination, distribution or duplication of this transmission by someone other than the intended addressee or its designated agent is strictly prohibited.

BIRCH, STEWART, KOLASCH & BIRCH, LLP8110 Gatehouse Road, Suite 100 East, P.O. Box 747, Falls Church, Virginia 22040-0747
Telephone: (703) 205-8000 **Facsimile:** (703) 205-8050

Application No. 10/593,036

Docket No.: 1592-0165PUS1

PROPOSED CLAIM AMENDMENTS – NOT FOR ENTRY

1. (Currently Amended) An InP substrate for epitaxial growth,
wherein, when haze is defined as a value calculated by dividing intensity of scattered light obtained when light is incident from a predetermined light source onto a surface of the InP substrate, by intensity of the incident light from the light source, the light source having a wavelength of 488 nm, every portion of an effectively used area measured by Surfscan 6220 exhibits a haze of not more than 1ppm, the InP substrate having a size of at least two inches; and
wherein the InP substrate comprises
~~the haze is not more than 1 ppm all over an effectively used area of the InP substrate and~~
an off-angle with respect to a plane direction ~~[[is]]~~ of 0.05 to 0.10°, ~~wherein the effectively used area includes the surface area of the substrate, with the exception of the peripheral part including the chamfered part of the substrate.~~
2. (Cancelled)
3. (Cancelled)
4. (Previously Presented) The InP substrate as claimed in claim 1, wherein a dislocation density is not more than $1000/\text{cm}^2$.
5. (Previously Presented) The InP substrate as claimed in claim 4, wherein the dislocation density is not more than $500/\text{cm}^2$.

Application No. 10/593,036

Docket No.: 1592-0165PUS1

6. (Previously Presented) A compound semiconductor substrate for epitaxial growth, comprising an InP substrate and at least one epitaxial layer on the InP substrate, wherein:
- the InP substrate has an off-angle with respect to a plane direction of 0.05 to 0.10° ,
 - the InP substrate has a haze of 0.5 to 0.8 ppm, and
 - the haze in a surface of the at least one epitaxial layer is not more than 1 ppm,
- wherein haze is defined as a value calculated by dividing intensity of scattered light obtained when light is incident from a predetermined light source onto the surface of the at least one epitaxial layer or a surface of the InP substrate, by intensity of the incident light from the light source.
7. (Previously Presented) An InP substrate for epitaxial growth,
- wherein, when haze is defined as a value calculated by dividing intensity of scattered light obtained when light is incident from a predetermined light source onto a surface of the InP substrate, by intensity of the incident light from the light source,
- the haze is not more than 1 ppm all over an effectively used area of the InP substrate, and
 - an off-angle with respect to a plane direction is 0.05 to 0.10° .
8. (New) A method to reduce haze on a surface of an epitaxial layer grown on an InP substrate, comprising:
- epitaxially growing a semiconductor layer on the InP substrate according to claim 1.
9. (New) An InP substrate for epitaxial growth,

Application No. 10/593,036

Docket No.: 1592-0165PUS1

wherein, when haze is defined as a value calculated by dividing intensity of scattered light obtained when light is incident from a predetermined light source onto a surface of the InP substrate, by intensity of the incident light from the light source, the light source having a wavelength of 488 nm, every portion of an effectively used area of the substrate exhibits a haze of not more than 1ppm;

wherein the InP substrate has a size of at least two inches, and comprises an off-angle with respect to a plane direction of 0.05 to 0.10°.

Partial translation of standard configuration specification
of Surfscan 6220 (revised)

page 1, item 3. ABOUT THIS DEVICE

This device is designed to perform a detection of the number or amount, the position, and the size of extraneous substances, particles, damages, and the like, on a mirror-polished bare silicon wafer or on a wafer on which a film is formed, by a laser scanning method. The obtained data can be displayed and analyzed by a database embedded in the main body of this device.

page 3, item 5. BASIC SPECIFICATION

- Wafer size applicable to this device

This device is compliant to SEMI and JEIDA standards.

- wafer diameter of 2-6 inches

Wafers of both orientation flat type and notch type are applicable.

[Partially Omitted]

- Wafer transfer system

[Partially Omitted]

(2-inch and 3-inch wafers are applicable by the device being attached with optional supplies of factory shipment)